

MP 104

TECHNICAL DATA



Cabinet and pedestal

Dimensions (HxWxD)	1 630 x 470 x 295 mm (64.2" x 18.5" x 11.6").
Weight	105/110 kg (232/243 pounds).
Construction	
- Roof/back: SS-EN2333.	3 mm (0.12") stainless steel
- Sides: steel.	2 mm (0.08") LDX stainless steel.
Vault design	
- Side steel	3 mm (0.12").
- Cash vault door	6 mm (0.24") armoured steel.
- Locking plates	6 point locking mechanism. Drill protection.
Compliance	EN12414

Environmental conditions

Operating temp.	
- Solar	-15 °C to 60 °C (0 °F to 140 °F).
- Mains with heater	-35 °C to 60 °C (-31 °F to 140 °F).
Relative humidity	Up to 95 %.

Electrical data

Power consumption	230 V / 115 V
- Mains operation	0.2 A / 0.4 A
- One heater	0.5 A / 1 A
- Two heaters	1 A / 2 A
Battery operation	12 V DC *
Solar operation	13 W to 25 W **

Data

Data storage	1024 KB static RAM.
Transactions storage	Up to 16 MB.
Transaction backup	5000 latest transactions.

Interfaces

Interfaces, standard	2 x RS232, 2 x PC card slots.
Interfaces, optional	1 x RS232, 1 x RS485. 8 relay input circuits. 8 relay output circuits.

*) Period of operation depends on ticket purchase volumes.

***) Operation time on battery depends on the size and position of the solar panel and the geographical location.



CALE

Payment

Magstripe cards	Swipe and insertion readers.
Chip/smart cards	Supported.
EMV	Chip no PIN/Chip&PIN supported in various countries.
Coin verifier	15 coin types, 3 tolerance ranges.
Coin slot	Mechanical coin slot shutter with inductive loop.
Escrow volume	0.2 l (6.8 ounces).
Coin box volume	4.6 l (155 ounces) with SW-controlled overflow protection.

Operation

Push buttons	Magnetically actuated. Reed switches.
Keypad Internal:	Mechanical-stroke. External: Vandal resistant.
Display	2 x 20 characters. 2 programmable LEDs. – Yellow (warning). – Red (alarm).

Receipt printer

Printer type	Thermoelectric.
Capacity	Up to 9000 per roll.
Characters	Proportional font, up to 80 characters/line.
Paper cutter	Complete cutting.
Take ticket sensor	Optional.

Communication

GPRS Supported.

LAN Supported.

Type of data	Transactions, blacklists, tariffs, parameters, statistics, alarms, etc.
--------------	---


Network

No. of nodes	Up to 10.
Applications	MEMO and real-time payment (shared database).

Central administration

Software Sale	WebOffice, hosted Software as a Service (SaaS) solution.
---------------	---

Measurements (in mm)



Specifications are subject to change without notice.



CALE AUSTRALIA PTY. LTD.

Phone (08) 9275 2634

austsales@caleaccess.com.au

www.caleaccess.com.au

Unit 3, 4 Bookham Street Morley WA 6062